

**INSTRUMENT SHEET**

Manufacturer: \_\_\_\_\_

Instrument Name / Model No.: \_\_\_\_\_

General Information	
Hazard Type	
Instrument Life Expectancy	
Instrument Type	
Manufacturer	
Sensor Types	
Display	
Battery Type	
Dimensions-Stripped	
Dimensions with Accessories	
Low Battery Indication	
Weight (with/without Accessories)	
Warranty	
Approval Standard (s)	

Date Management	
Data Logging Memory	
Computer Interface	
Software Required to Access Data (Version)	

Instrument Performance	
Continuous Operating Time **	
Battery Operating Time	
Sampling Rate	
Response Time T <sub>90</sub>	
Response Time T <sub>50</sub>	
Start-up to T <sub>90</sub> after 24-hour Storage	
Start-up to T <sub>90</sub> after 7-day Storage	
Start-up to T <sub>90</sub> after 30-day Storage	

Safety	
Hazardous Area Rating & Classification	
Ingress Protection Rating	

Error-State Notification	
High/Low Temperature	
High/Low Humidity	
Over Range	
Pump Flow Restriction	

Maintenance	
Bump Test Interval	
Calibration Interval	
Factory service Interval	
Instrument Life Expectancy	

Instrument Readings	
Instantaneous Reading Frequency	
STEL	Yes / No
TWA	Yes / No
Peak	Yes / No
Alarms/Indicators	
Alarm Set Points	

\*\* Refer to SESS Manual, 3.2.8

Revision # (Date): \_\_\_\_\_